



## ASSEMBLY INSTRUCTIONS #24316 Easy-Up® Power Max Cart

### Package Contents:

DESCRIPTION	QTY
A. Large Washers (D35*d13*2.7t)	2
B. Tires 8 x 1.75"	2
C. Nylon Lock Nut	2
D. Open End Wrenches	2
E. Cotter Pins (2.5*40)	2
F. 3/8-16 Hex bolts	2
G. Bow-tie Locking Cotter Pins	2
H. Detent Ring Pins	2
I. Allen wrench	1
J. Small Washers (D20*d10.5*2.0t)	2
K. 1/4-20 screws	4
Upper frame w/ handle	
Center section of frame	
Lower section of frame w/basket	



**!** To assemble, check to ensure that all necessary parts are included. Please follow the assembly instructions carefully.

### Step One

1. Set the lower section of the frame on the floor with the basket side up.
2. Slide a tire onto the axle with the plastic spacer towards the center.
3. Install one large washer on the outer side of the tire and secure with a cotter pin.
4. Repeat with the second tire.

### Step Two

1. Insert the center section of the frame on the inside of the triangle supports. The flat side of the center cross support bar should face the front of the cart.
2. Line up the holes and insert the 3/8" hex bolts into the lower holes on each side. The head of the hex bolt should be on the outer side of the frame. Install a small washer and nylon lock nut and tighten with the enclosed open end wrenches.
3. Insert the detent ring pins into the top holes and secure with bow-tie locking cotter pin. The ring side of the pin should be on the outer side of the frame.

### Step Three

1. Insert the upper frame onto the center section of the frame. The handle should be facing the back side of the cart. Line up the holes and insert a 1/4-20 screw into each hole. Tighten with the enclosed Allen wrench.

If you have any questions or concerns, please contact customer service toll free at 1-800-365-1311, or e-mail [service@sstack.com](mailto:service@sstack.com).